

The Brain.

Setting parameters easily
and having all information
available at a glance.

Method Test				
Test Status:	Test running			Sample Countdown:
Current Task:	Wait for interval			4:51
Nominal Temperature:	37.0			<input type="button" value="Lift Position"/>
Actual Temperature:	37.0			<input type="button" value="Abort"/>
Interval:	1/2			<input type="button" value="Print"/>
Interval Repeat:	1/2			<input type="button" value="ITM"/>
Method:	Test			
Batch No.:	123			
Product:	Product			
Bath Temp	ext. Sensor	Stirrer Speed	User	17/09/14
37.0	23.1	100	Factory	17:43:00

**PHARMA
TEST**

PTWS 820D

Tablet Dissolution Tester



The new 8-station PTWS 820D tablet dissolution bath meets in all details the current specifications of the USP, EP and JP. The long-term and reliable operation includes well engineered, stable mechanics.

Advantages

- › More space in the operating area
- › Precise alignment of the test vessels and stirring tools
- › Large, clear LCD screen
- › Completely new concept in method management
- › Data security protection
- › CAN bus technology
- › Higher energy efficiency

The unit is based on a sturdy aluminum base plate to which the lifter and mechanical head are attached. The user can easily program the reproducible lift positions. The new design of the lifter eases access to the dissolution vessels. All eight test vessels are accessible from all sides of the unit. This facilitates trouble-free removal of the samples and the input of the dissolution media. The touch sensitive screen allows operation even when wearing protective gloves, since it responds to pressure. The quick test "Short-Cut" option to start a measurement is possible without any restrictions; using only a few entries, a test can be started. Data is stored on an SD-card allowing almost unlimited storage.



Specifications

- › Fully USP and EP compliant
- › Backlit color touch screen
- › 8 programmable stirrer immersion positions
- › Two different vessel arrangements possible (4 by 2 or 2 by 4)
- › User management with password control
- › External heating system
- › Speed control: 25-250 RPM
- › Energy saving, programmable "Wake Up" heater function and "Sleep Mode"
- › Pump for water circulation and 1500 W heater for fast heat up
- › Built-in-calibration procedures
- › All CE/EMC certification provided
- › All IQ & OQ documents included



Further information is available at
www.pharma-test.com/ptws-820d

With the CAN bus technology all relevant data can be processed and transferred from all connected control units and sensors are tested. Detected errors are stored or, if possible, corrected immediately. The control program allows the instrument administrator or device users to define and allocate these rights. The mechanical qualification of the device is supported by the system program. The user can define an "Infinity Test" time. The bath temperature and the stirrer speed can be user defined. The heating system produces a 30% faster heating rate of the water, which in turn leads to an increase in available testing time. For the first time a "Sleep" mode has been introduced to control the heating system. The instrument can shut down both the heater and the circulation pump, if the unit is inactive for long periods. The system automatically switches itself back on until the set temperature is reached.

Options

- › Eco-conscious double-walled water bath
- › EPE-820 motorized sampling system
- › ITM-820 media temperature monitoring system
- › TM-820 & TMA-820 manual and automated tablet drop magazine
- › PT-RP80 serial report printer
- › Full range of certified validation tools available